



**WATER SERVICES ASSOCIATION
OF AUSTRALIA**

**Conduit Inspection
Reporting Code of Australia**

WSA 05—2008

Second Edition

Version 2.2

May 2008

ORIGINATED AS AUSTRALIAN CONDUIT CONDITION EVALUATION MANUAL 1991
REVISED AND REDESIGNATED AS WSA 05—2002 SEWER INSPECTION REPORTING CODE OF AUSTRALIA
REPLACES WSA 05—2006 VERSION 2.1

COPYRIGHT

CONTENTS

ACKNOWLEDGMENTS

FOREWORD

PREFACE

AN EVOLUTIONARY PROCESS

CODE PURPOSE AND SCOPE

MANDATORY AND INFORMATIVE

INDUSTRY TRAINING

PROPOSED AMENDMENTS

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

1.2 DEFINITIONS

1.2.1 Adjusting construction

1.2.2 Asset owner

1.2.3 Benching

1.2.4 Blister

1.2.5 Breaking

1.2.6 Breaking-Displaced

1.2.7 Breaking-Missing

1.2.8 Breaking-Exceptional

1.2.9 Bulge

1.2.10 Collapse

1.2.11 Chamber

1.2.12 Chamber unit

1.2.13 Combined system

1.2.14 Conduit

1.2.15 Conduit unit

1.2.16 Conduit unit length

1.2.17 Connection

1.2.18 Exfiltration 5

1.2.19 Feature

1.2.20 Finished surface level

1.2.21 Fracturing

1.2.22 Grade

1.2.23 Gravity system

1.2.24 Groundwater

1.2.25 Infiltration

1.2.26 Inflow

1.2.27 Inspection length

1.2.28 Inspection shaft

1.2.29 Invert

1.2.30 Joint

1.2.31 Junction

- 1.2.32 Landing
 - 1.2.33 Maintenance hole
 - 1.2.34 Maintenance shaft
 - 1.2.35 Maintenance structure
 - 1.2.36 Node
 - 1.2.37 Operator
 - 1.2.38 Outfall
 - 1.2.39 Pressure main
 - 1.2.40 Receiving water
 - 1.2.41 Rehabilitation
 - 1.2.42 Repair
 - 1.2.43 Roots-Beard
 - 1.2.44 Sewage
 - 1.2.45 Sewer
 - 1.2.46 Sewerage
 - 1.2.47 Shaft
 - 1.2.48 Shear displacement
 - 1.2.49 Soffit
 - 1.2.50 Spalling
 - 1.2.51 Subsoil drain
 - 1.2.52 Surface cracking
 - 1.2.53 Surface water
 - 1.2.54 Taper
 - 1.2.55 Wall cracking
- 1.3 REFERENCED DOCUMENTS
- 1.4 ABBREVIATIONS

SECTION 2 REQUIREMENTS FOR THE CONDUCT OF INSPECTIONS

- 2.1 GENERAL
- 2.2 TRAINING AND ACCREDITATION OF PERSONNEL
 - 2.2.1 Operators
 - 2.2.2 Asset managers and contract managers
- 2.3 PLANNING THE INSPECTION
- 2.4 PREPARATION OF SEWERS
- 2.5 CCTV CAMERA
 - 2.5.1 General
 - 2.5.2 Capability
 - 2.5.3 Picture quality
- 2.6 CAMERA OPERATION
 - 2.6.1 Camera position
 - 2.6.2 Camera speed
- 2.7 LINEAR MEASUREMENT
- 2.8 DATA DISPLAY DURING VIDEO PLAYBACK
- 2.9 MAXIMUM DEPTH OF FLOW
- 2.10 INSPECTION REPORT

- 2.10.1 General
- 2.10.2 Operator's report
- 2.10.3 Video record
- 2.10.4 Photographs
- 2.10.5 Video clips
- 2.10.6 Preliminary grading of internal condition

SECTION 3 INSPECTION OF CONDUITS — THE DESCRIPTION AND ENCODING OF OBSERVATIONS

3.1 PURPOSE

3.2 METHODS OF INSPECTION

3.3 CONDUITS — CODING SYSTEM

3.4 CONDUITS — HEADER INFORMATION

- 3.4.1 Recording of information
- 3.4.2 Mandatory information
- 3.4.3 Optional information
- 3.4.4 Information to be provided by the asset owner

3.5 ENCODING OF OBSERVATIONS

- 3.5.1 General
- 3.5.2 Observation codes
- 3.5.3 Main observation codes
- 3.5.4 Sub-codes
 - 3.5.4.1 Characterisation sub-codes
 - 3.5.4.2 Quantification sub-codes
 - 3.5.4.3 Circumferential location
 - 3.5.4.4 Observation associated with a joint
 - 3.5.4.5 Longitudinal location
 - 3.5.4.6 Continuous features
 - 3.5.4.7 Photograph reference
 - 3.5.4.8 Video location reference
 - 3.5.4.9 Video clips
 - 3.5.4.10 Specific remarks
- 3.5.5 Logging procedures
 - 3.5.5.1 Defining location and direction of inspection
 - 3.5.5.2 Start of inspection
 - 3.5.5.3 Finish of inspection
 - 3.5.5.4 Inspection abandoned
 - 3.5.5.5 Inspection recommenced
 - 3.5.5.6 Features occupying the full circumference
 - 3.5.5.7 Features suspected but not observed
 - 3.5.5.8 Multiple features

3.6 CONDUIT HEADER CODES

- 3.6.1 General
- 3.6.2 Header codes to describe the location of the inspection
- 3.6.3 Header codes for reporting inspection details
- 3.6.4 Header codes for recording conduit details
- 3.6.5 Header codes for recording miscellaneous information
- 3.6.6 Change of codes for header information

3.7 CODES FOR REPORTING THE INSPECTION OF CONDUITS

- 3.7.1 General
 - 3.7.1.1 Additional observations to be recorded
- 3.7.2 Codes relating to the structural integrity of conduits
 - 3.7.2.1 Cracking—C
 - 3.7.2.2 Fracturing—F
 - 3.7.2.3 Breaking—B
 - 3.7.2.4 Deformation—D
 - 3.7.2.5 Collapsed conduit—X
 - 3.7.2.6 Surface damage—S
 - 3.7.2.7 Soil visible through defect—SV
 - 3.7.2.8 Void visible through defect—VV
 - 3.7.2.9 Porous conduits (pipes)—PP
- 3.7.3 Codes specific to brick and masonry conduits
 - 3.7.3.1 Displaced bricks—DB
 - 3.7.3.2 Missing bricks—MB
 - 3.7.3.3 Dropped invert—DI
 - 3.7.3.4 Brick separation—BS
 - 3.7.3.5 Brick conduit collapsed—XB
 - 3.7.3.6 Missing mortar—MM
- 3.7.4 Codes relating to the blockage and leakage of conduits
 - 3.7.4.1 Deposits on the wall and in the invert—DE
 - 3.7.4.2 Exfiltration—EX
 - 3.7.4.3 Infiltration—I
 - 3.7.4.4 Obstruction—OB
 - 3.7.4.5 Ingress of soil—ING
 - 3.7.4.6 Roots—R
- 3.7.5 Codes relating to the performance of joints and jointing material (seals)
 - 3.7.5.1 Displaced joint—JD
 - 3.7.5.2 Jointing material (seal) intrusion—JI
 - 3.7.5.3 Weld defect—W
- 3.7.6 Codes relating to connections and junctions
 - 3.7.6.1 Connection—CN
 - 3.7.6.2 Intruding connection—CI
 - 3.7.6.3 Defective connection—CX
 - 3.7.6.4 Junction—JN
 - 3.7.6.5 Defective junction—JX
- 3.7.7 Codes relating to linings and repairs
 - 3.7.7.1 Lining defective—PL
 - 3.7.7.2 Point repair—RP
 - 3.7.7.3 Defective repair—RX
- 3.7.8 Codes relating to miscellaneous observations concerning the construction and performance of the conduit
 - 3.7.8.1 Flow in incoming conduit—IF
 - 3.7.8.2 Line of conduit deviates—L
 - 3.7.8.3 Vermin—V
- 3.7.9 Miscellaneous codes relating to the administration of the inspection
 - 3.7.9.1 Start node—ST
 - 3.7.9.2 Finish node—FH
 - 3.7.9.3 General comment—GC
 - 3.7.9.4 General photograph—GP
 - 3.7.9.5 General video clip—GV
 - 3.7.9.6 Flow (water) level—WL
 - 3.7.9.7 Atmosphere in the conduit—GAS

3.7.9.8 Loss of vision—LOV

3.7.9.9 Inspection (Survey) abandoned—SA

3.7.10 Codes for changing header information

3.7.10.1 Change photographic volume reference—AC

3.7.10.2 Change of lining—LC

3.7.10.3 Change of conduit material—MC

3.7.10.4 Change in conduit unit length—PC

3.7.10.5 Change in precipitation—RC

3.7.10.6 Change of cross section—SC

3.7.10.7 Change video volume reference—TC

3.8 INTERPRETATION OF INSPECTION RESULTS

3.8.1 General

3.8.2 Interpretation of inspection results for operating sewers

3.8.3 Interpretation of inspection results for newly constructed sewers and drains

SECTION 4 INSPECTION OF MAINTENANCE STRUCTURES — THE DESCRIPTION AND ENCODING OF OBSERVATIONS

4.1 PURPOSE

4.2 METHODS OF INSPECTION

4.3 MAINTENANCE STRUCTURES — CODING SYSTEM

4.4 MAINTENANCE STRUCTURES—HEADER INFORMATION

4.4.1 Recording of information

4.4.2 Mandatory information

4.4.3 Optional information

4.4.4 Information to be provided by the asset owner

4.5 ENCODING OF OBSERVATIONS

4.5.1 Recording of information

4.5.2 Main observation codes

4.5.3 Characterisation codes

4.5.4 Quantification codes

4.5.5 Circumferential location

4.5.6 Observation at a joint

4.5.7 Descriptive location

4.5.8 Vertical location

4.5.9 Continuous feature

4.5.10 Photograph reference

4.5.11 Video location reference

4.5.12 Remarks

4.6 LOGGING REQUIREMENTS

4.7 HEADER CODES FOR THE INSPECTION OF MAINTENANCE STRUCTURES

4.7.1 General

4.7.2 Codes for location of inspection

4.7.3 Codes for inspection details

4.7.4 Header codes for recording maintenance structure details

4.7.5 Header codes relating to the administration of the inspection

4.8 CODES FOR REPORTING THE INSPECTION OF MAINTENANCE STRUCTURES

4.8.1 Codes relating to the structural integrity of the structure

- 4.8.1.1 Cracking—HC
- 4.8.1.2 Fracturing—HF
- 4.8.1.3 Breaking—HB
- 4.8.1.4 Deformation—HD
- 4.8.1.5 Collapsed structure—HX
- 4.8.1.6 Surface damage—S
- 4.8.1.7 Soil visible through defect—HSV
- 4.8.1.8 Void visible through defect—HVV
- 4.8.1.9 Porous wall—HPP
- 4.8.1.10 Ingress of soil—HIN
- 4.8.1.11 Roots—HR
- 4.8.2 Codes specific to brick and masonry structures
 - 4.8.2.1 Displaced bricks—HDB
 - 4.8.2.2 Missing bricks—HMB
 - 4.8.2.3 Brick separation—BS
 - 4.8.2.4 Missing mortar—HMM
 - 4.8.2.5 Brick maintenance structure collapsed—HXB
- 4.8.3 Codes relating to connections and their flows
 - 4.8.3.1 Intruding connection—HCI
 - 4.8.3.2 Connection type—HCN
 - 4.8.3.3 Connecting conduit—HCP
 - 4.8.3.4 Defective connection—HCX
 - 4.8.3.5 Flow in connecting conduit—HIF
 - 4.8.3.6 Sealed conduit through maintenance structure—HSP
- 4.8.4 Codes relating to observations made above the benching
 - 4.8.4.1 Corrosion barrier layer defect—HCB
 - 4.8.4.2 Defective cover or frame—HCF
 - 4.8.4.3 Cross section of chamber—HCS
 - 4.8.4.4 Deposits on walls and landings—HDE
 - 4.8.4.5 Grit trap under cover—HGT
 - 4.8.4.6 Infiltration—HI
 - 4.8.4.7 Surface damage—HS
 - 4.8.4.8 Defective step or ladder—HSL
 - 4.8.4.9 Evidence of surcharge—HSU
 - 4.8.4.10 Weld failure—HW
- 4.8.5 Codes relating to joints and jointing
 - 4.8.5.1 Displaced joint—HJD
 - 4.8.5.2 Intruding sealing material—HJI
- 4.8.6 Codes relating to linings and repairs
 - 4.8.6.1 Defective lining—HLD
 - 4.8.6.2 Point repair—HPR
 - 4.8.6.3 Defective repair—HRX
- 4.8.7 Codes relating to observations of the benching, channel and main flow
 - 4.8.7.1 Benching—HBE
 - 4.8.7.2 Channel—HCH
 - 4.8.7.3 Deposits on walls, invert, benching and landings—HDE
 - 4.8.7.4 Hydraulic performance—HHP
 - 4.8.7.5 Other obstacles—HOB
 - 4.8.7.6 Safety bars and chains—HSC
 - 4.8.7.7 Silt trap in invert—HST
 - 4.8.7.8 Flow (Water) level—HWL
- 4.8.8 Miscellaneous observations
 - 4.8.8.1 Exfiltration—HEX
 - 4.8.8.2 Flow control—HFC

- 4.8.8.3 Atmosphere within the maintenance structure—HGA
- 4.8.8.4 General comment—HGC
- 4.8.8.5 General photograph—HGP
- 4.8.8.6 Vermin—HV
- 4.8.9 Miscellaneous codes relating to the administration of the inspection
 - 4.8.9.1 Inspection (Survey) abandoned—HAS
 - 4.8.9.2 Inspection completed—HFH
 - 4.8.9.3 Loss of vision—HLV
- 4.8.10 Codes for changing header information during an inspection
 - 4.8.10.1 Change video volume reference—CEA
 - 4.8.10.2 Change photograph volume reference—CEB
 - 4.8.10.3 Change of material—CED
 - 4.8.10.4 Change of chamber unit length—CEE
 - 4.8.10.5 Change in precipitation—CEF
 - 4.8.10.6 Change in type or material of steps or ladders—CEG

APPENDIX A THE RELATIONSHIP BETWEEN EN 13508 AND THIS CODE

APPENDIX B FORMAT FOR ELECTRONIC TRANSFER OF CODED DATA

APPENDIX C MANUAL CODING SHEET

APPENDIX D ACRONYMS

APPENDIX E SCORING OF DEFECTS AND THE PRELIMINARY GRADING OF APPARENT CONDITION OF SEWERS

APPENDIX F SPECIFICATION FOR CCTV INSPECTION ACCEPTANCE CRITERIA FOR NEWLY CONSTRUCTED SEWERS AND STORMWATER DRAINS

F1 INTRODUCTION

F2 CCTV INSPECTION REQUIREMENTS

F3 QUALIFICATIONS OF CCTV OPERATORS

F4 ACCEPTANCE REPORTING

F5 WORK AS CONSTRUCTED

F6 ACCEPTANCE CRITERIA TABLES

F7 PIPE MATERIALS

APPENDIX G SAMPLE ILLUSTRATION OF TYPICAL DEFECTS AND FEATURES SHOWN IN COMPENDIUM

APPENDIX H DEFECT EXPLANATIONS FOR CRACKING, FRACTURING, BREAKING AND COLLAPSE OF RIGID CONDUITS

H1 GENERAL

H2 CRACKED CONDUITS

H3 FRACTURED PIPES

H4 BROKEN CONDUITS

H5 COLLAPSED CONDUITS

APPENDIX I SUMMARY OF MAIN CODES FOR DESCRIBING CONDUIT CONDITION

APPENDIX J SUMMARY OF MAIN CODES FOR DESCRIBING MAINTENANCE STRUCTURES

APPENDIX K AMENDMENT FORM

TABLES

| | |
|-----|---|
| 2.1 | MAXIMUM DEPTH OF FLOW AT COMMENCEMENT OF INSPECTION |
| 3.1 | VALUES OF CLOCK FACE REFERENCES |
| 4.1 | TYPICAL RECORD OF VERTICAL CRACK |
| 4.2 | TYPICAL RECORD OF LATERAL CONNECTION |
| B1 | FIELD IDENTIFIER CODES |
| B2 | INSPECTION DATA FIELD CODES |
| D1 | MATERIAL ACRONYMS |
| D2 | LINING MATERIAL ACRONYMS AND APPLICABLE LINING TECHNIQUES |
| E1 | STRUCTURAL DEFECT SCORES – PIPE SEWERS – RIGID MATERIALS |
| E2 | STRUCTURAL DEFECT SCORES – PIPE SEWERS – FLEXIBLE MATERIALS |
| E3 | STRUCTURAL DEFECT SCORES – BRICK SEWERS |
| E4 | SERVICE DEFECT SCORES – ALL SEWERS |
| E5 | STRUCTURAL GRADING THRESHOLDS – ALL SEWERS |
| E6 | SERVICE GRADING THRESHOLD – ALL SEWERS |
| F1 | ACCEPTANCE CRITERIA FOR RIGID STORMWATER DRAINS – STEEL REINFORCED CONCRETE, FIBRE REINFORCED CEMENT |
| F2 | ACCEPTANCE CRITERIA FOR FLEXIBLE STORMWATER PIPES – PVC, PE, POLYPROPYLENE, PROFILED STEEL |
| F3 | ACCEPTANCE CRITERIA PIPE AND FITTING CONFIGURATION – ALL STORMWATER DRAINS |
| F4 | ACCEPTANCE CRITERIA FOR RIGID SEWERS – VITRIFIED CLAY, STEEL REINFORCED CONCRETE |
| F5 | ACCEPTANCE CRITERIA FOR FLEXIBLE SEWER PIPES – PLASTICS (PVC, PE, PP, GRP), DUCTILE IRON (DICI) AND STEEL (SCL) |
| F6 | ACCEPTANCE CRITERIA PIPE AND FITTING CONFIGURATION – ALL SEWERS |

FIGURES

| | |
|-----|--|
| 1.1 | ILLUSTRATION OF TERMS RELATING TO MAINTENANCE HOLES |
| 3.1 | EXAMPLES OF CLOCK FACE REFERENCES |
| 3.2 | REFERENCE POINTS FOR LONGITUDINAL LOCATION |
| 4.1 | CLOCK FACE REFERENCES IN SHAFTS OF MAINTENANCE STRUCTURES |
| B1 | EXAMPLE OF DATA TRANSFER FORMAT USING AUSTRALIAN AND NEW ZEALAND CODES |